



# Profoto B10x Plus Duo kit

## Specifications

### Flash Head

|                        |   |
|------------------------|---|
| Maximum Power          | 500 Ws  |
| Power Control          | 10 Stops  |
| Flash Duration         | t.1: 1/14,000 to 1/390 Sec<br>t.5: 1/35,000 to 1/1200 Sec |
| Recycle Time           | 0.05 to 2.2 Sec   |
| Color Temperature      | 3000 to 6500K   |
| Flash Ready Indicator  | Audio, Visual   |
| Accessory Fitting Type | <i>None</i>   |

### Modeling Light

|         |      |
|---------|------|
| Type    | LED  |
| Wattage | 24 W |

### Sync

|                            |                        |
|----------------------------|------------------------|
| Sync Type                  | Button, Optical, Radio |
| Built-In Wireless Receiver | Yes                    |
| Wireless Range             | 328.1' / 100 m (Radio) |
| System Connection          | USB-C                  |

## Power

Power Source

External Battery

## Battery

Battery Chemistry

Lithium-Ion

Flashes Per Charge

200 Flashes (Full Power)

Recharge Time

90 Minutes

## General

Display

LCD

Mount

5/8" / 16 mm Receptacle

Dimensions

H: 9.3 x W: 4.3 x L: 3.9" / H: 23.5 x W: 11.0 x L: 10.0 cm

Weight

4.2 lb / 1.9 kg, Including Battery